

Code No.	Part No.	Description
1	L-104	Amplifier Chassis with Lettering
2	L-36	Bottom Cover
3	F-262	Terminal Strip
4	F-266	Terminal Strip
5	F-1189	Terminal Strip
6	F-1503	Receptacle - 2 Pole
7	F-267	Octal Socket
8	F-1292	Capacitor (Electrolytic) (40 Mfd) (450 Mfd) (15 Mfd) (450 Volts)
9	F-1685	Capacitor (Electrolytic) (15 Mfd) (450 Volts) (10 Mfd) (450 Volts) (20 Mfd) (150 Volts)
10	F-1686	Capacitor (Electrolytic) (20 Mfd) (150 Volts) (20 Mfd) (150 Volts)
11	F-1285	Adaptor Plate
12	F-627	Terminal Strip
13	H-261	Relay
14	F-1671	Switch
15	F-1249	Knob
16	F-861	Thermal Fuse Holder
17	S-720A	Cartridge Fuse (2 Amperes)
18	L-136	Transformer - Output
19	L-137	Transformer - Power
20	F-1689	Speaker Connection Chart
21	F-273	6SN7-GT Tube
22	F-1072	6L6-G Tube
23	F-195	5U4-G Tube
24	S-500K	Cord and Plug
25	S-2321A	Strain Relief
26	S-104D	Resistor (1,200 ohms) (Half Watt)
27	S-102F	Resistor (1.0 megohm) (Half Watt)
28	S-104K	Resistor (22,000 ohms) (Half Watt)
29	S-102A	Resistor (47,000 ohms) (Half Watt)
30	S-102B	Resistor (150,000 ohms) (Half Watt)
31	S-102G	Resistor (220,000 ohms) (Half Watt)
32	S-102L	Resistor (330,000 ohms) (Half Watt)
33	S-102K	Resistor (470,000 ohms) (Half Watt)
34	S-102D	Resistor (2.2 megohms) (Half Watt)
35	S-102N	Resistor (3,300 ohms) (Half Watt)
36	S-103A	Resistor (1,200 ohms) (One Watt)
37	S-103F	Resistor (68,000 ohms) (One Watt)
38	S-105A	Resistor (680 ohms) (Two Watt)
39	S-110C	Resistor (150 ohms) (Five Watt) Resistor (150 ohms) (Four Watt)
40	S-110B	Resistor (6,000 ohms) (Four Watt)
41	S-114B	Resistor (15,000 ohms) (Ten Watt)
42	S-104U	Resistor (47 ohms) (Half Watt)
43	S-104N	Resistor (150 ohms) (Half Watt)
44	S-210J	Capacitor (.003 Mfd) (600 Volts)
45	S-210B	Capacitor (.002 Mfd) (600 Volts)
46	S-210K	Capacitor (.004 Mfd) (600 Volts)
47	S-210E	Capacitor (.005 Mfd) (600 Volts)
48	S-210P	Capacitor (.05 Mfd) (600 Volts)
49	S-210A	Capacitor (.02 Mfd) (600 Volts)
50	S-210F	Capacitor (.001 Mfd) (600 Volts)
51	S-210N	Capacitor (.01 Mfd) (600 Volts)
52	S-200A	Capacitor (.0002 Mfd) (400 Volts)
53	S-200C	Capacitor (.0005 Mfd) (500 Volts)
54	H-235	Potentiometer (Volume Control) (0-35,000 ohms)
55	F-1799	Knob (Volume Control)
56	H-717	Box (Volume Control)
57	F-719	Bracket (Volume Control)
58	F-1673	Cartridge - Crystal Pickup (Includes No. 59) for 78 RPM Recordings (E-40 Only)
	F-2527	Crystal & Stud Ass'y. (Includes No. 59) for 45 RPM Recordings (E-80 & E-120 Only)
	F-463	Cartridge - Crystal Pickup (Includes No. 59) for 45 RPM Recordings (Converted 40-Selection Mechanism Only)
59	F-506	Needle - Precious Metal Tip (For F-1673)
	F-427	Needle - Jewel Tip (For F-1673)
	F-426	Needle - Precious Metal Tip (For F-2527 & F-463)
	F-428	Needle - Jewel Tip (For F-2527 & F-463)

Model E